



NOTE:

1. ALL DIMENSIONS ARE IN MILLIMETERS.
THE UNSPECIFIED DIMENSION TOLERANCES ARE PLUS/MINUS 0.5.
ACTIVE AREA DIMENSIONS: 340(L) × 272(W)
VIEWABLE AREA DIMENSIONS: 340(L) × 272(W)
PROFILE DIMENSIONS: 388.5(L) × 320.5(W) × 8.2(D).
2. SPECIFICATION:

- ① TECHNICS HOLE: $6-\phi 2.5$.
- ② DUST-PROOF FRAME, MATERIAL: ALUMINUM.
- ③ 8X19 HOUSING MATES WITH CONTROLLER HOUSING MATERIAL: PBTU.94V-0(BLACK)
- ④ CABLE OUTER LAYER MATERIAL: PVCBG01RUBBER.
- ⑤ GROUND LINE.
- ⑥ GLASS BOARD, THICKNESS: 6.

CONNECTION CHART

PIN	SIGNAL	INSULATION COLOR	OVERALL SHIELD
1	GND		
2	KEY		
3	Y-in2	BLUE	
4	Yout	BLUE	
5	Y-in1	BLACK	
6	GND	YELLOW	
7	GND		
8	GND	GREEN	
9	X-in2	WHITE	
10	Xout	RED	
11	X-in1	RED	
12	KEY		